

Champion Effluent Pumps

**Champion
Pump**

CPES

**1/3-1/2HP
EFFLUENT/SUMP**

Every pump tested in water to ensure pump meets performance curve.



FEATURES/BENEFITS

PERFORMANCE

Heads up to 37' TDH
Flows up to 72 GPM

MOTOR

High efficient, 115v, oil filled, permanent split capacitor motor with upper and lower ball bearings and thermal overload protection

- Constant bearing lubrication
- Maximum motor cooling
- Runs cooler and lasts longer
- Internal overload protection
- Quiet operation
- Fasteners and shaft made from rugged, corrosion resistant stainless steel

SEAL DESIGN

Mechanical with secondary dynamic lip seal

- Provides added leakage protection

IMPELLER DESIGN

Non-clog style vortex impeller

- Designed to help reduce clogging by foreign material

POWER CORD

Sealed entry quick disconnect power cords

- Prevents water from entering the motor housing through a cut cord
- Easy to replace in the field
- Available in lengths up to 100'

SWITCH

Piggy-back switch design

- Defective switches can be diagnosed over the phone
- Pump can be operated manually or supplied with other piggy-back switches
- Switch can be replaced without having to replace the pump

APPLICATIONS

Basements, dewatering, septic systems, residential and commercial developments and elevator pits



Wide-Angle Float

Vertical Float

1/3-1/2 HP submersible pumps that handle up to 3/4" solids with 2" discharge with 1 1/2" adapter

5 Year Limited Warranty

Distributed By:



**E3055 County Road J
Kewaunee, WI 54216
(920) 362-2437
www.vangoethemseptic.com**